Product Data Sheet

GW85302S

On request



Thermoplastic indoor and outdoor floodlight in smoke grey color with hot galvanized bracket painted teh same color of the body. Equipped with graduate scale to facilitate orientation. Flat tempered glass 4 mm thickness silk screen printed; hinged to the body for quick access inside the floodlight. Anti-aging silicone gasket. Power input through PG 11 for cables Ø 5.5 ÷ 9.5 mm. Optic in 99.85% polished and anodised aluminium. Electrical componenent plate in galvanized steel. Quick wiring bipolar terminal block for cable 2,5mm².

Application	Indoor / Outdoor	IP degree	IP65
Mechanical resistance	IK09	Insulation class	II
Glow Wire Test	650 °C	Maximum surface exposed to the wind	0.072 m²
Minimum distance from the illuminated object	1 m	Weight (kg)	3.7
Colour	Smoke grey	Voltage	230 V - 50 Hz
Lamp power	70 W	Lamp current	1 A
Lamp holder	RX7s	Lamp supplied	SD
Lamp included	Yes	Efficiency class of the lamp supplied	A+
Efficiency class of compatible lamps	A+	Optic	Symmetrical
Light pollution	0 cd/Klm	Warranty	5 years
Electrocod	2443		

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY

IP
IP65

IK
IK09

GWT
650 °C

0.072 m²

1 m

STANDARDS/APPROVALS

CE

Data, measures, designs and pictures are for information purpose only, last update 16/04/2024. They can be changed at any moment, therefore it is always ecommended to read the last updated version published on the website www.gewiss.com.Lumen output and system power are subject to a tolerance of +/- 10%. Unless stated otherwise, the values apply to an ambient temperature of 25°C. Terms of warranty at https://www.gewiss.com/it/en/company/landingpage/led-warranty. - 1 of 1