


Série URBAN [O3]




Urban decorative in die-cast aluminum EN AB 46100 powder poliester painted after epoxi surface treatment and phosphochromating process, with lateral ventilation system by technopolimer grid. Recessed handle closing system and steel holding cable. External screw stainless steel AISI 316. Anti ageing silicone gasket. Double two poles safety knife for wires 2,5 mm². PC holding components plate. Internal wiring with UG4G4 1mmq wires. Modular LED engines (2-4) with injected aluminum heat sink equipped with PMMA lenses. Side fixing for Ø60mm bracket in die-cast aluminum with possibility of ±15° inclination adjustment. It can be used up to 50 ° C of ambient temperature but with reduced currents as indicated in the Technical Manual.

Série	URBAN [O3]	Óptica	Ciclopedonal - ULOR: 0%
Numero moduli	3 (3X16 LED)	Temperatura de cor	4000 K (CRI>70)
Temperatura de uso	-25 +35 °C	Potência de sistema	81 W
Lúmen saída (lm)	8060	Vida útil LED (L80B10)	100000 h
Vida útil LED (L90B20)	50000 h	Tensão	220 / 240 V - 50 / 60 Hz
Peso (kg)	10.3	Cor	Cinza grafite
Overvoltage resistance	Common mode: 8KV; Differential mode: 6KV		

DIMENSIONAL



PHOTOMETRIC DISTRIBUTION



TECHNICAL SYMBOLOGY



STANDARDS/APPROVALS

